



Performance comparison of GES DISC data as a service between server-based system and Cloud Computing platform

Long Pham¹, Aijun Chen^{1,2}, Eric Winter³, Christopher Lynnes¹

Contact: Long Pham long.b.pham@nasa.gov

1NASA Goddard Earth Sciences Data & Information Services Center (GES DISC); 2Center for Spatial Information Science and Systems, George Mason University; 3Wyle Information Systems, at GES DISC

Introduction

The NASA Goddard Earth Science Data and Information Service Center (GES DISC) recently demonstrated and evaluated the provision of (1) "Data-as-a-Service" in the Goddard Space Flight Center (GSFC) Cloud platform using OPENDAP (Open-source Project for a Network Data Access Protocol) protocols; (2) "Data-processing-as-a-Service" using GrADS Data Server (GDS), and (3) "Data-analysis-as-a-Service" using NASA Giovanni (GES DISC Interactive Online Visualization ANd aNalysis Infrastructure). The latter was also evaluated on the commercial Cloud of Amazon Web Service (AWS)

The work entailed porting OPeNDAP to the NASA GSFC Cloud, along with a selected set of data (AIRS/Aqua, OMI/Aura, TRMM, and MERRA*), and then exercising the server using several clients from different network. The evaluation included the following aspects of using open source software in the Cloud to serve large volumes of satellite data for public access and subsetting.

- · Ease of porting and operating OPeNDAP, GDS, and Giovanni in Cloud (e.g., time needed to setup one instance)
- Performance factors, including accessibility, stability, speed, and scalability. as compared with existing GES DISC capabilities.

*AIRS: Advanced Infrared Sounder; OMI: Ozone Monitoring Instrument

TRMM: Tropical Rainfall Measuring Mission; MERRA: Modern-Era Retrospective Analysis for Research and Applications Ported Software: OPeNDAP, GDS, Giovanni

The following applications were ported on the NASA GSFC Cloud Platform and Amazon EC2 (Elastic Cloud Computing) platform

A. OPeNDAP - Data Access-as-a-Service

OPENDAP is an open source data service. It provides a way to easily share science data across the internet. It is widely used in earth-science research settings and supports multiple commonly used data format including HDF4/5, NetCDF3/4, CSV, and ASCII, It facilitates Earth Science data online sharing and access and makes data online access convenient to scientists. The OPeNDAP 1.7.0 was installed and tested on the NSAS GSFC Cloud and Amazon EC2 platform.

B. GrADS Data Server (GDS) -- (Data Processing-as-a-Service)

GDS is a data server providing stable and secure subsetting and analysis services across the Internet. The GDS 2.0 was installed and tested.

C. Giovanni -- (Data Analysis-as-a-Service)

Giovanni is an interactive Web-based application for visualizing, analyzing, and accessing vast amounts of Earth science satellite data. There are different Giovanni portals available for various kinds of satellite data, e.g. MODIS, AIRS, OMI, CloudSat, etc.

Test Data for OPeNDAP

Four satellite data products were selected as test data for OPeNDAP (25 granules each), as listed in the following table:

Data	Server	Input Data Format/	Output Data Format/	
Products	Specification	Size (MB)/granule	Size (MB)/granule	
OMI/Aura	Local: 16 cores * 2.4GHz 32GB RAM	HDF5/5.62	NetCDF/68.46	
TRMM	Same as above	HDF/81.14	NetCDF/81.25	
AIRS/Aqua	Same as above	HDF/110	NetCDF/296.86	
MERRA	Same as above	HDF/312.63	NetCDF/792.27	
All 4 data products	Cloud: 4 cores * 2.8GHz/23GB RAM	Same Input/Output as the above.		


Performance Comparison of OPeNDAP


25 granules for each product were pre-staged to the Cloud platform and used to exercise the OPeNDAP server. The OPeNDAP data transfer performance and stability were estimated and compared between the local system and the Cloud platform in different network environment.

20

OMI

TRMM





Comparison of the processing speed of the OPeNDAP on

Cloud VM1 based on requests from local, VM2 and SEN

AIRS

MERRA

40 1616 13 6019 17 5037

16.7945 10.0649 9.3749

---Cloud VM1

localhost (MB/s)

-Cloud VM2 --:

VM1 (MB/s)

Cloud VM1 SEN

Cloud VM1


-Benchmark (MB/S)


TRMM AIRS MERRA

59.2827 39.8284 35.9395 40.4947

34.0597 24.8471 26.9628 30.5896

14.8182 12.3857 11.8934 16.3794





57.05 40.4229 35.2985 38.6285

68.46 81.25 296.9 792.3



Cloud VM1 localhost test4 (MB/s)

Cloud VM1 localhost test1 (MR/s) 63 38889 39 8284 35 5947 42 481

Cloud VM1 localhost test2 (MB/s) 52.66154 37.7907 35.8094 41.6327

Cloud VM1 localhost test3 (MB/s) 61.125 40.8291 36.5141 42.5494

Cloud VM1 localhost test5 (MB/s) 61.67568 39.6341 36.0267 42.5266

Cloud VM2: Cloud Virtual Machine 2, same configuration as VM1 SEN: NASA network of 1GB

Cloud & Benchmark Localhost SEN


Localhost

Cloud VM1 (MB/S)

Benchmark (MB/S)

Performance Comparison of GDS

TRMM data was used to test and compare the data processing performance of GDS between local system and Cloud platform. We used area average algorithm.




Hardware specifications:


Server	CPU (GHz)	Num. of Cores	RAM (GB)	Notes
Benchmark	2.4 * 4	16	32	AMD 6136
Cloud VM1	2.8 * 1	4	34.2	Intel X5660

Performance Comparison of Giovanni 4


Giovanni 4 was used to test data analysis in Cloud platform as a case of Data Analysis as a Service and the feasibility of porting long-term legacy-based system

to the Cloud platform.





Server	CPU (GHz)	Num. of Cores	RAM (GB)
Benchmark	2 * 4	16	32
EC2 small Inst.	2.8 * 1	4	34.2
EC2 big Inst.	2.8 * 1	8	68.4



^{*} Go-CART: Goddard Chemistry Aerosol Radiation and Transport, a tropospheric aerosol model.

Conclusions and Future Work

A. It is feasible to port legacy satellite data and information services, both simple and complicated ones, to the Cloud platform although the porting process is time-consuming: B. Cloud computing has better performance, compared with local systems, mostly because

Cloud computing has better dedicated servers and better networks; C. The elasticity of provisioning on-demand multi-cores-oriented resources in the Cloud

platform should potentially provide significant advantages to complicated analysis-oriented and computing-intensive applications. This work is ongoing.

Acknowledgements: Thanks the Goddard Information Technology & Communications Directorate for providing the Cloud platform. Authors affiliated with Center for Spatial Information Science and Systems (CSISS), George Mason University have a cooperative agreement with GES DISC (Center Director: Dr. Liping Di).